

(12) 按照专利合作条约所公布的国际申请

(19) 世界知识产权组织
国际局



(43) 国际公布日
2006年3月23日 (23.03.2006)

PCT

(10) 国际公布号
WO 2006/029570 A1

(51) 国际专利分类号⁷: F04B 47/06, E21B 43/00
(21) 国际申请号: PCT/CN2005/001471
(22) 国际申请日: 2005年9月13日 (13.09.2005)
(25) 申请语言: 中文
(26) 公布语言: 中文
(30) 优先权:
200410050431.5
2004年9月17日 (17.09.2004) CN

(71) 申请人及
(72) 发明人: 冯春国(FENG, Chunguo) [CN/CN]; 中国辽宁省沈阳市新城子区杭州西路沈阳新城石油机械厂, Liaoning 110121 (CN)。刘忠亚(LIU, Zhongya) [CN/CN]; 中国辽宁省沈阳市于洪区张士开发区3号街12甲6号, Liaoning 110141 (CN)。

(74) 代理人: 沈阳科苑专利商标代理有限公司 (SHENYANG PATENT & TRADEMARK AGENCY ACADEMIA SINICA); 中国辽宁省沈阳市和平区三好街24号, Liaoning 110004 (CN)。

(81) 指定国 (除另有指明, 要求每一种可提供的国家保护): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK,

DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW。

(84) 指定国 (除另有指明, 要求每一种可提供的地区保护): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), 欧亚 (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), 欧洲 (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)。


根据细则4.17的声明:

— 关于申请人有权要求在先申请的优先权 (细则4.17(iii)) 对以下指定国 AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM,

[见续页]

(54) Title: A NC RECIPROCATING IMMERSIBLE OIL PUMP

(54) 发明名称: 数控往复式潜油泵装置



(57) Abstract: An oil pump used in deep well especially a nc reciprocating immersible oil pump, which can integrate a power equipment and the oil pump and adjust the parameter on-line, comprises a balance sieve tube, a power equipment and the oil pump, all of which are immersed in the ground oil, wherein the power equipment comprises a stator having a seal chamber and a rotor including an iron core and installed in the stator, the stator and the rotor constitute a friction pair through a supporting sleeve and the rotor core. The upper end of the stator links to the lower end of the oil pump connecting an oil outlet tube, the lower end of the stator links to the sieve tube in turn. In this application a rod and an oil pump overground are not used, therefor the fixing time and the cost are reduced, at the same time the enegy cost are decreased too.

[见续页]

WO 2006/029570 A1